

Specification / Spesifikasi / 规格

PROPERTIES / KANDUNGAN / 性质	MS EN 413 - 1:2012 MC 12.5
Fineness - 90 um Residue (%) Kehalusan - 90 um Residue (%) 细度 - 90 um 余留(%)	15 Max
Initial Setting Time (minutes) Masa Penetapan Permulaan (minit) 初凝时间 (分钟)	60 Min
Sulfate Content, SO ₃ (%) Kandungan Sulfat, SO ₃ (%) 三氧化硫含量, SO ₃ (%)	3.5 Max
Chloride Content, Cl (%) Kandungan Klorida, Cl (%) 氯离子含量, Cl (%)	0.10 Max
Air Content (%) Kandungan Udara (%) 空气含量 (%)	8 - 22
Water Retention (%) Pengekalan Air (%) 保水率 (%)	80 Min
Soundness (Expansion) (mm) Kekukuhan (Pengembangan) (mm) 稳健性 (膨胀) (mm)	10 Max
Compressive Strength Mortar Cubes / Kekuatan Mampatan / 抗压强度 2 days / hari / 天 (N/mm ²) 28 days / hari / 天 (N/mm ²)	7 Min 12.5 - 32.5

Specification of product is subjected to manufacturer's change without prior notice.
Spesifikasi produk adalah tertakluk pada perubahan oleh pengeluar tanpa notis awal.
厂商有权更改产品规格, 无需另行通知。

Recommended Mix Proportion / Jumlah Campuran Yang Disyorkan / 推荐的混合比例

Application / Applikasi / 应用	Parts of Tasek Masonry Cement / Jumlah Isipadu Tasek Masonry Cement / 所需的大石牌砌灰水泥分量 (KG)	Parts of Sand By Volume / Jumlah Isipadu Pasir / 所需的沙份量	
		Min / 最少	Max / 最多
Plastering / Kerja Plaster / 涂灰	1	3	5



Packaging / Pembungkusan / 包装

50 kgs bag / Beg 50kg / 50公斤包装

Tasek Corporation Berhad

Corporate Office
6th Floor, Office Block
Grand Millennium Kuala Lumpur
160, Jalan Bukit Bintang
55100 Kuala Lumpur, Malaysia
Tel: 603-2144 6868
Fax: 603-2144 6828
Website: www.tasekcement.com

Cement Manufacturing Plant
Lot 5, Persiaran Tasek
Tasek Industrial Estate
31400 Ipoh
Perak, Malaysia
Tel: 605-291 1011
Fax: 605-291 9932

Marketing Office and Distribution Centre
Lot 1552, Kg Jaya Industrial Area
Off Jalan Hospital
47000 Sungai Buloh
Selangor, Malaysia
Tel: 603-6156 6818
Fax: 603-6157 8868



MASONRY CEMENT



www.tasekcement.com



TASEK CORPORATION BERHAD

MASONRY CEMENT

Tasek Masonry Cement is the brand name for masonry cement specially formulated and manufactured to achieve the required properties and workability for plastering purposes. It is produced by using high quality Portland cement clinker grinding with plasticizing materials and air entraining agent in a controlled environment to assure product consistency and performance.

Tasek Masonry Cement complies with the Malaysian Standard MS EN 413-1:2012.

Tasek Masonry Cement adalah jenama simen penampal yang dirumus khas dan dihasilkan untuk mencapai sifat-sifat dan kebolehkeraan untuk kerja-kerja penampalan. **Tasek Masonry Cement** dihasilkan dengan mengisarkan klinker simen Portland serta bahan-bahan plaster dan agen pengedap udara dalam keadaan yang terkawal untuk memastikan kualiti produk yang konsisten.

Tasek Masonry Cement menepati piawaian yang ditetapkan oleh Standard Malaysia MS EN 413-1:2012.

Tasek Masonry Cement 是大石公司生产的砌筑水泥品牌。它的独特配方使它有效的提高工作性。**Tasek Masonry Cement** 采用了高品质的水泥熟料，可塑料和引气剂研磨而成以确保产品的品质和一致性。

Tasek Masonry Cement符合马来西亚标准局MS EN 413-1:2012 的标准和规格。



Applications / Penggunaan / 产品用途

It is highly recommended for interior and exterior plastering works

Sesuai digunakan untuk kerja penampalan plaster dalaman dan luaran

极力推荐用于户内，户外抹灰和外墙修饰

Advantages / Kelebihan / 产品优点

- Easy to mix / *Senang diguna* / 容易使用
- Good workability / *Kebolehkeraan yang baik* / 提高工作性
- Good bonding / *Lekatan yang baik* / 良好的粘接
- Improved surface finishing /
Meningkatkan kelicinan hasil permukaan / 表面平滑修整

